

# SAFFTY DATA SHFFT

Liquid Diamond Revision Date 7/21/2016

SECTION – 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name Liquid Diamond Item L[

Product Use Aircraft Paint Sealant

Company Name Jet Stream Aviation Products Office (972) 542-2400

1971 University Business Dr. Suite 102 Fax (972) 542-0238

McKinney Tx 75071 **Web** <u>www.jetstreamproducts.com</u>

EMERGENCY TELEPHONE NUMBER INFOTRAC (800) 535-5053

SECTION – 2 HAZARDS INFORMATION

Physical Hazards FLAMMABLE LIQUIDS-Category 3
Health Hazards STOT SINGLE EXPOSURE-Category 3

Environmental ACUTE-Aquatic Toxicity-Category 2; CHRONIC-Aquatic Toxicity-Category 2

Flammables



Narcotic Effects

Warning

Flammable liquid and vapor, (Vapor may flash when heated in present of flame, Liquid does not sustain combustion, Not Regulated by DOT)

May cause drowsiness or dizziness

May cause eye or skin irritation, May be harmful if swallowed, Do not get in eyes, on skin, or clothing, and avoid inhalation, or inhale dust, Do not smoke, eat or drink while using, Use personal protective equipment as required, and adequate ventilation, Wash thoroughly with soap and water after handling, Avoid release into the environment

SECTION - 3 COMPOSITION INFORMATION (Exact percentage of the listed chemicals of composition has been withheld as a trade secret)

CHEMICAL NAME
Mineral Spirits

COMMON NAME AND SYNONYMS

Stoddard Solvent, Short-range Mineral Spirits

(Exact percentage of the listed chemicals of composition has been withheld as a trade secret)

CAS # IMPURITIES

PERCENT

8052-41-3

20 - 30%

SECTION - 4 FIRST AID MEASURES

EYE CONTACT Immediately flush eyes with cold water for several minutes while lifting upper and lower eyelids. Remove contact

lenses if present and easy to do without injury to the eye and continue rinsing, If irritation persists seek medical aid

SKIN CONTACT Wash contaminated skin with plenty of soap and water, Remove any contaminated clothing and wash before reuse, If

irritation occurs or persists seek medical aid

**INHALATION** Move person to fresh air, if they have problem breathing, show signs of overexposure or feel unwell obtain medical

attention

INGESTION DO NOT INDUCE VOMITING. If person is fully conscious, rinse mouth out and give one to two glasses of water to

dilute and obtain immediate medical attention

Aspiration Hazard Not considered to be an aspiration hazard due to product viscosity. If swallowed, vomiting may occur spontaneously,

but DO NOT INDUCE. If vomiting occurs, keep head below hips to prevent aspiration into the lungs

**ACUTE SYMPTOMS OF SINGLE OVEREXPOSURE** 

Eyes May cause eye irritation
Skin May cause skin irritation

Inhalation Dust may cause irritation, Vapor or fumes may cause mild irritation

**Ingestion** May be harmful if swallowed

CHRONIC SYMPTOMS OF PROLONGED OR REPEATED OVEREXPOSURE

Eyes May cause eye irritation, discomfort, redness, tearing, burning sensation

Skin May cause skin irritation, itching, redness, burning, drying or cracking

Inhalation Dust may cause irritation, Vapor or fumes may cause irritation, headache, dizziness or drowsiness, May affect target

organs

Ingestion May be harmful if swallowed, May cause irritation, of the mouth, and throat, May affect target organs

SECTION – 5 FIRE FIGHTING MEASURES

Extinguishing Media Use DRY chemicals, CO2, alcohol foam. Water spray to cool or protect exposed materials

Hazardous Decomposition Burning or thermal decomposition can produce, carbon monoxide, carbon dioxide, and other toxic fumes

**Reactive With**Reactive with, strong oxidizing agents, strong bases, strong acids **Explosion Hazards**Containers may erupt when heated excessively during a fire

Static DischargeMay ignite productMechanical ImpactNot applicable

Protective Equipment Use MSHA/NIOSH approved self-contained breathing apparatus and full protective gear

#### SECTION – 6 ACCIDENTAL RELEASE MEASURES

Emergency Procedures Warn personnel of spill

Personal Precautions Eliminate ignition sources and ventilate area, Avoid slipping on spilled product

Protective Equipment Safety Glasses, Gloves

Containment Use sand or inert non-combustible absorbent pads to prevent spill from spreading

Clean Up Procedures Do not flush liquid in public sewer, water systems or surface waters, Recover as much as possible and absorb

remainder with inert material, Place into labeled containers and store in safe locations for proper disposal, Mop

area with clean water

Disposal Dispose of material in accordance with all State and Federal Guidelines and Regulations

## SECTION – 7 HANDLING AND STORAGE

Handling Keep away from incompatible materials, heat, sparks, electrical equipment, fire and all ignition sources, Use

appropriate safety equipment, and adequate ventilation, Avoid eye or skin contact and inhalation of mist, vapor or fumes, Avoid inhalation of dust, May be harmful if swallowed, Do not smoke, eat or drink while using, Wash

thoroughly after handling, Avoid release to the environment

Storage KEEP OUT OF REACH OF CHILDREN, Keep container closed when not in use, Store in a cool dry place away

from incompatible materials, Store away from heat, sparks, open flames or hot surfaces, Store below 49°C

(120°F) and in accordance with Class II Combustible Liquids (GHS Category 3)

Incompatible Materials Incompatible with, strong oxidizing agents, strong bases, strong acids

# SECTION – 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS					Significant
CHEMICAL NAME	ACGIH (TWA 8)	ACGIH (STEL)	OSHA PEL (TWA 8)	OSHA (CEIL)	Exposure
Mineral Spirits	100 ppm (525 mg/m³)		500 ppm (2900 mg/m³)		CNS

### PERSONAL PROTECTIVE EQUIPMENT



Chemical Safety Glasses, Goggles or Face Shield



Impervious Chemical Gloves



Dust Mask

## **Ventilation**



General Ventilation

If exposure limits listed above are exceeded, or irritation is experienced, use a MSHA / NIOSH approved dust mask or respirator

# **HMIS HAZARD RATINGS**

Health 1
Flammability 2
Reactivity 0
Personal Protection E

# SECTION - 9 PHYSICAL AND CHEMICAL PROPERTIES

Flash Point	53.8°C (128.9°F) - Pensky-Marten Closed Cup	Specific Gravity / Density	1.15
Flammable Limits	Does not sustain combustion (ASTM D4206)	pH (± 0.3)	ND
Auto-Ignition Temp.	ND	Viscosity	ND
Physical State	Viscous Liquid	Freeze Point	-14°C (-26°F)
Appearance	Opaque Tan	Boiling Point	ND
Odor	Light Solvent	Vapor Density (air=1)	ND
Odor Threshold	ND	Vapor Pressure (mm Hg)	ND
Solubility	< 70%	Evaporation Rate (nBuAc=1)	ND
Volatiles	< 88%	Partition Coefficient	ND
VOC	< 30%	Molecular Weight (g/mol)	ND
LVP-VOC	0.0%	<b>Decomposition Temperature</b>	ND

# SECTION – 10 STABILITY AND REACTIVITY

Reactivity (Specific Test Data) None available

Chemical Stability Stable under normal ambient and anticipated conditions of use

Hazardous Polymerization Will not occur

Conditions To Avoid Heat sources, sparks, flame or static discharge and incompatible materials Incompatible Materials Incompatible with, strong oxidizing agents, strong bases, strong acids

Thermal Decomposition Burning or thermal decomposition can produce, carbon monoxide, carbon dioxide, and other toxic fumes

#### SECTION – 11 TOXICOLOGICAL INFORMATION

# **ROUTES OF EXPOSURE**

Eyes (Yes), Skin (Yes), Ingestion (Yes), Inhalation (Yes "Vapor, Fumes or Dust")

#### **ACUTE SYMPTOMS OF SINGLE OVEREXPOSURE**

Eyes May cause eye irritation
Skin May cause skin irritation

Inhalation Dust may cause irritation, Vapor or fumes may cause mild irritation

Ingestion May be harmful if swallowed

#### CHRONIC SYMPTOMS OF PROLONGED OR REPEATED OVEREXPOSURE

Eyes May cause eye irritation, discomfort, redness, tearing, burning sensation

Skin May cause skin irritation, itching, redness, burning, drying or cracking

Inhalation Dust may cause irritation, Vapor or fumes may cause irritation, headache, dizziness or drowsiness, May affect target

organs

Ingestion May be harmful if swallowed, May cause irritation, of the mouth, and throat, May affect target organs

Acute Tox Calculated Oral: > 5,000 mg/kg Dermal: > 5,000 mg/kg Inhaled: > 20.0 mg/L

Acute Tox Category Not applicable (Oral >5000 mg/kg), Not applicable (Dermal >5000 mg/kg), Not applicable (Inhaled >20 mg/L) Vapors

Additional Info

Target Organs Kidneys, Respiratory Tract, Lungs, Skin, Central Nervous System, Eyes

Medical Conditions Preexisting, eye, skin, kidney, respiratory, lung, disorders may be aggravated by exposure to this product

Notes to Physician In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption, Contains

petroleum distillates, vomiting may cause aspiration pneumonia

# **CARCINOGENIC – This product contains concentrations above 0.1% of the following:**

 CHEMICAL NAME
 NTP
 ACGIH
 IARC
 GHS Category

 None Listed
 NA
 NA
 NA
 NA

None Listed NA NA NA NA

MUTAGENIC AND REPRODUCTIVE EFFECTS – This product contains concentrations above 0.1% of the following:

CHEMICAL NAME Germ Cell Mutagenicity Toxic to Reproduction

None Listed NA NA

#### **COMPONENTS ACUTE TOXICITY**

CHEMICAL NAME	<u>Type</u>	<u>Form</u>	<u>Subject</u>	Result Value	Exposure Time	GHS Category
Mineral Spirits	LD50	Oral	Rat	5,000 mg/kg		(>2000 mg/kg)
	LD50	Inhaled	Rat	11 mg/L	4 Hours (Mist)	(>5 mg/L)
	LD50	Dermal	Rabbit	> 3,000 mg/kg		(>2000 mg/kg)

SECTION - 12	ECOLOGICAL INFORMATION				
CHEMICAL NAME	<u>Type</u>	Subject Subject Latin	Result Value	Exposure Time	<b>GHS Category</b>
Mineral Spirits	LD50	Bluegill Sunfish (Lepomis macrochirus)	4.2 mg/L		2 (>1, ≤10 mg/L)
	EC50	Water Flea (Daphnia magna)	2.3 mg/L		2 (>1, ≤10 mg/L)
	EC50	Green Algea (Pseudokirchnerella s.)	1.2 mg/L		2 (>1, ≤10 mg/L)

Presistence And Degradability Hydrocarbons from this product which do partition to air are expected to rapidly photodegrade

Bioaccumulative Potential There is no evidence to suggest bioaccumulation will occur

Mobility In SoilThis material is a partially mobile liquidOther Adverse EffectsToxic to aquatic life with long lasting effects

#### SECTION – 13 DISPOSAL CONSIDERATIONS

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER Dispose of any waste in accordance with all State and Federal Guidelines and Regulations

#### **ENVIRONMENTAL FATE**

Under RCRA rules, it is the responsibility of the user of the product to determine, at the time of disposal, whether the material is a hazardous waste

Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate, or otherwise inappropriate

### SECTION – 14 TRANSPORT INFORMATION

#### **DOT CLASSIFICATION**


UN Number Proper Shipping Name n.o.s. (Chemicals ) or "Limits"

Ltd Qty "Limited Quantity" "Inner packaging not over 5.0 Liters (1.3 gallons)"

<u>Hazard Class</u> <u>Packing Group</u> <u>Label Codes</u> <u>Reportable Quantity (lbs)</u> <u>Response</u> <u>Marine Pollutant</u> <u>Hazard Label</u> <u>Secondary</u>

None None None None 128 No Additional Info: Shipping information for: (Pints, Quarts and Gallons), Liquid does not sustain combustion by the

prescribed procedure in the 49 CFR §173.120(b)(3)



#### SECTION - 16 OTHER INFORMATION LEGEND DESCRIPTION **SDS ACGIH** American Conference of Governmental Industrial Hygienists LC50 A concentration that is lethal to 50% of a given species in a given time CAS Chemical Abstracts Service Registry LD50 Dose that is lethal to 50% of a given species by a given route of exposure CEIL Ceiling Limit (15 minutes) LEL Lower Explosive Limit CERCL Comprehensive Environmental Response, Compensation, and Liability Act Liver Damage LD CI Cochlear Impairment NΑ Not Applicable CNS Central Nervous System ND Not Determined Concentration of a chemical that gives half-maximal response FC50 NFPΔ National Fire Protection Association NIOSH **EPA Environmental Protection Agency** National Institute for Occupational Safety and Health Eye (EI = Irritation) (ED = Damage) (EV = Visual Impairment) NE Not Established FRG Full Bunker Gear NTP National Toxicology Program GHS Globally Harmonized System OSHA Occupational Safety and Health Administration HAP California Hazardous air pollutant Clean Air Act **PEL** Permissible Exposure Limit (OSHA) Peripheral Nervous System HMIS-A Safety Glasses PNS California Priority Pollutant under the Clean Water Act HMIS-B Safety glasses, gloves PP HMIS-C Safety glasses, gloves, chemical apron REL Recommended exposure limit (NIOSH) HMIS-D Face shield, gloves, chemical apron RT Upper Respiratory Tract HMIS-E Safety glasses, gloves, dust respirator Skin (SI = Irritation) (SD = Damage) (SA = Absorption) (SS = Sensitizer) HMIS-F Safety glasses, gloves, chemical apron, dust respirator SARA Superfund Amendments and Reauthorization Act HMIS-G Safety glasses, gloves, vapor respirator STFI Short Term Exposure Limit (15 minutes) HMIS-H Splash goggles, gloves, chemical apron, vapor respirator TC Lo Lowest concentration that is toxic to a given species in a given time

# Jet Stream Aviation Products

HMIS-X Ask Supervisor

HS

KD

HMIS-I Safety glasses, gloves, dust and vapor respirator

Kidney Damage (nephropathy)

HMIS-K Air line hood or mask, gloves, full chemical suit, boots

HMIS-J Splash goggles, gloves, chemical apron, dust and vapor respirator

California Hazardous Substance under the Clean Water Act

and nCites LLC have compiled the information herein from sources believed to be reliable and up-to-date, and is accurate to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources or the completeness and expressly do not make warranties, nor assume any liability for its use. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever for any and all injuries, losses, or damages to persons or property arising from the use of this product or information.

TD Lo

TI V

**TSCA** 

TWΔ

UEL

ΤP

Print Date 7/22/2016

**Supersedes Safety Data Sheet Dated** 

Lowest dose that is toxic to a given species

California Toxic Pollutant under the Clean Water Act

Threshold Limit Value (ACGIH)

Toxic Substances Control Act

Upper Explosive Limit

Time Weighted Average (8 hours)